



# Polyflag B1 - SB

100g/m<sup>2</sup>

**Material Description** 100% PES / Polyester Flag media for which is tear proof and transparent. The paperback release liner with PTA glue can be teared off easily after printing. Flame retardant B1.

- Qualifications**
- 100% PES incl. Polyurethan / Acrylate
  - Paperback release liner (easy tear off)
  - B1 fire retardant
  - Tear proof & transparent
  - Cold cut
  - Available in 54+, 60+x 50m






- Details**
- Suitable printing condition: temperature 15-30°C / humidity 30-60%
  - Proper temperature of printer heating zone is around 30 °C
  - Ambient temperature and weather can affect the condition of the product

- Applications**
- Commercial flags
  - Beach flags
  - Banners

|                            |              |                                       |
|----------------------------|--------------|---------------------------------------|
| <b>Physical Properties</b> | Quality      | 100% PES incl. Polyurethan / Acrylate |
|                            | Backing      | Paper backing                         |
|                            | Weight       | 100 g/m <sup>2</sup>                  |
|                            | Adhesive     | PTA gleu                              |
|                            | Print side   | White Satin finish                    |
|                            | Reverse side | Paper backing                         |
|                            |              |                                       |
|                            |              |                                       |
|                            |              |                                       |
|                            |              |                                       |
|                            |              |                                       |

**Compatibility**

HP Latex LX 800/820/850  
 HP Expedio 3200/5000 UVC  
 Durst Rho ( UV curable)  
 Vutek Ultra Vu 33xx / 53xx  
 (Solvent)

-  Heavy solvent
-  Eco Solvent
-  Mild Solvnet
-  Latex
-  UV curable

And more...

Make your own practical test to be sure it reaches your quality standard. For all- and latest information see our Compatibility List.

**Printing guidelines** Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

**Colour profiles** ATgraphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists who can produce your profile if it's not direct available from our library. Please contact us for the possibilities.

**Storage conditions** 1 year under normal conditions (10. 25°C at a relative humidity of 30. 75 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

**Environment** The media and final prints can be disposed of as PET Material is suitable for recycling. Please consult local recycle resources.

Data presented in this product information serve only as a guide-line for compatibility and use. ATgraphix will assume no liability in connection with any use of this information. Technical specifications are subjected to change without prior notice. ATgraphix, The Netherlands. www.atgraphix.com