



Satin Paper 135

135 g/m²

Material Description Outdoor billboard wet strength paper for premium quality (almost photographic) indoor and outdoor applications.

Due the coated surface of the paper, high quality photo printing is outstanding. High colour brilliance, saturated colors and excellent edge definitions.

- Qualifications**
- Wet strength billboard quality
 - Quality is confirmed by "Allgemeine Plakatiergesellschaft APG+- Swiss
 - Print side: semi-gloss matt white surface
 - Reverse side: White.
 - Good wet strength and dimensional stability
 - High tear resistance and high opacity, also when wet.
 - Perfect density for city lights

Details Can be pasted with conventional starch-type billboard glue (Henkel Zellura UST 3500) Please, read the technical instructions of Henkel. If new glues or other procedures for gluing the paper are to be used, it is recommended to carry out some practice tests.

- Applications**
- In and out door bill boards
 - In and outdoor posters
 - City lights
 - Long term outdoor advertisements

Physical Properties

| | | |
|---------------|--|-------------------------------|
| Quality | | Premium Outdoor quality paper |
| Paper quality | | Wet strength type |
| Weight | | 135 g/m ² |
| Thickness | | 0.13 mm |
| Print side | | White satin |
| Reverse side | | Off-white |
| | | |
| | | |
| | | |
| | | |

- Compatibility**
- Nur**
Vutek
Hewlett Packard
Roland
Mimaki
Mutoh
And more
- Eco Solvent
 - Solvent
 - Latex
 - UV-curable
 - UV-curable Led
 - Water
 - Oil
 - Dye-sublimation

Make your own practical test to be sure it reaches your quality standard. For all- and latest information see our Compatibility List.

Printing guidelines Max. temperature (material) should not exceed 80°C as overheating can impair the flatness. Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

Colour profiles AT graphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists that can do profiling for almost every printer - rip combination.

Storage conditions 1 year under normal conditions (10. 25°C at a relative humidity of 30. 75 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

Environment The media and final prints can be disposed of as paper. Material is suitable for recycling. Please consult local recycle resources.

Data presented in this product information serve only as a guide-line for compatibility and use. AT graphix will assume no liability in connection with any use of this information. Technical specifications are subjected to change without prior notice. AT graphix Vianen, The Netherlands. www.atgraphix.com